

Model No.	Total cooling output L35 L35	Rated voltage, 50/60 Hz	Dimensions [mm]			Installation type		
			Width	Height	Depth	External mounting	Partial internal mounting	Full internal mounting
Blue e+ S, sheet steel*								
3178.800	300 W	110 - 240 V, 1~	300	570	159	■		■
3178.801	300 W	110 - 240 V, 1~	300	570	159	■		■
3179.800	520 W	110 - 240 V, 1~	300	570	199	■		■
3179.801	520 W	110 - 240 V, 1~	300	570	199	■		■
3180.800	780 W	110 - 240 V, 1~	300	570	250	■		■
3184.800	1,000 W	110 - 240 V, 1~	400	950	196	■		■
3184.840	1,000 W	380 - 480 V, 2~	400	950	196	■		■
Blue e+, sheet steel*								
3185.830	1,600 W	110 - 240 V, 1~ 380 - 480 V, 3~	400	950	310	■	■	■
3186.930	2,000 W	110 - 240 V, 1~ 380 - 480 V, 3~	450	1600	294	■	■	■
3187.930	2,600 W	110 - 240 V, 1~ 380 - 480 V, 3~	450	1600	294	■	■	■
3188.940	4,200 W	380 - 480 V, 3~	450	1600	393	■	■	
3189.940	5,800 W	380 - 480 V, 3~	450	1600	393	■	■	
Blue e+ for maritime and other dynamic applications*								
3184.837	1,000 W	110 - 240 V, 1~ 380 - 480 V, 3~	400	950	310	■		■
3185.837	1,600 W	110 - 240 V, 1~ 380 - 480 V, 3~	400	950	310	■		■
3186.937	2,000 W	110 - 240 V, 1~ 380 - 480 V, 3~	450	1600	294	■		■
3187.937	2,600 W	110 - 240 V, 1~ 380 - 480 V, 3~	450	1600	294	■		■
Blue e+, stainless steel*								
3185.530	1,600 W	110 - 240 V, 1~ 380 - 480 V, 3~	400	950	310	■	■	■
3186.630	2,000 W	110 - 240 V, 1~ 380 - 480 V, 3~	450	1600	294	■	■	■
3187.630	2,600 W	110 - 240 V, 1~ 380 - 480 V, 3~	450	1600	294	■	■	■
3188.640	4,200 W	380 - 480 V, 3~	450	1600	393	■	■	
3189.640	5,800 W	380 - 480 V, 3~	450	1600	393	■	■	
Blue e+, chemical*								
3185.835	1,600 W	110 - 240 V, 1~ 380 - 480 V, 3~	400	950	310	■	■	■
3186.935	2,000 W	110 - 240 V, 1~ 380 - 480 V, 3~	450	1600	294	■	■	■
3187.935	2,600 W	110 - 240 V, 1~ 380 - 480 V, 3~	450	1600	294	■	■	■
3188.945	4,200 W	380 - 480 V, 3~	450	1600	393	■	■	
3189.945	5,800 W	380 - 480 V, 3~	450	1600	393	■	■	
Blue e+ outdoor**								
3185.330	1,500 W	110 - 240 V, 1~ 380 - 480 V, 3~	467	1042	280	■	■	■
3186.330	2,000 W	110 - 240 V, 1~ 380 - 480 V, 3~	517	1692	260	■	■	■
3187.330	2,500 W	110 - 240 V, 1~ 380 - 480 V, 3~	517	1692	260	■	■	■
3188.340	3,800 W	380 - 480 V, 3~	517	1692	360	■	■	■
3189.340	5,000 W	380 - 480 V, 3~	517	1692	360	■	■	■
Blue e+, roof-mounted***								
3185.730	1,300 W	110 - 240 V, 1~ 380 - 480 V, 3~	700	308	560	■		

* Operating temperature range: -20 °C - +60 °C | IP protection category and UL Type: IP55, UL Type 12 and 3R | Integrated condensate evaporation except for 3178.801 and 3179.801

** Operating temperature range: -30 °C - +60 °C | IP protection category and UL Type: IP56, UL Type 12, 3R and 4 | Integrated condensate evaporation

*** Operating temperature range: -20 °C - +60 °C | IP protection category and UL Type: IP54, UL Type 12 | Condensate evaporation optionally available as an accessory

Technical specifications: www.rittal.com/wallmounting | Design software: www.rittal.com/therm | Enclosure configuration: www.rittal.com/configurators